



# Larsen's®

## Architectural Series Fire Extinguisher Cabinets Submittal and Detail Sheet

PROJECT: \_\_\_\_\_

LOCATION: \_\_\_\_\_

MODEL NUMBER: \_\_\_\_\_

QUANTITY: \_\_\_\_\_

ARCHITECT: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_

DATE: \_\_\_\_\_

DISTRIBUTOR: \_\_\_\_\_

### SPECIFICATIONS:

All recessed and semi-recessed cabinets and surface-mounted steel cabinets have a heavy gauge, white baked enamel box. Surface-mounted cabinets with aluminum door and trim have a box constructed entirely of clear or color anodized aluminum. Surface-mounted cabinets with stainless steel door and trim have a box constructed entirely of 304 stainless steel with a #4 finish.

Steel and stainless steel cabinets have a full 1/2" thick hollow metal heavy gauge door. Trims and doors feature one piece construction with satin finish pull handle, continuous matching hinge, and self-adjusting roller catch. Baked white enamel finish is standard for steel units. Stainless steel cabinets have a #4 finish, 304 stainless steel.

Aluminum cabinet doors and trims are extruded or fabricated aluminum with clear satin anodized finish. Aluminum door is 1/2" thick with satin finish matching pull handle and hinge. Color anodized finishes are available as options.

**STEP 1:** Select cabinet model number from the dimensions on page 2 and indicate on the top of this sheet. To specify aluminum trim and door, use the prefix, "AL" before the model number. To specify stainless steel trim and door, use the prefix, "SS" before the model number. **Note:** Rough opening dimensions are larger for fire-rated cabinets. Please refer to separate Fire-Rated Cabinet Submittal and Detail Sheet.

**STEP 2: Select Door Style and Door Glazing (if applicable) below:**

<input type="checkbox"/> Full Panel	<input type="checkbox"/> Horizontal Duo	<input type="checkbox"/> Vertical Duo	<input type="checkbox"/> Solid
<input type="checkbox"/> Full Panel with Larsen-Loc®	<input type="checkbox"/> Horizontal Duo with Larsen-Loc	<input type="checkbox"/> Vertical Duo with Larsen-Loc	<input type="checkbox"/> Solid with Larsen-Loc

**DOOR GLAZING:**

- Clear Acrylic (Standard)
- Clear Tempered Safety Glass
- Clear Wire Glass
- Laminated Safety Glass
- Bronze Acrylic
- Gray Acrylic
- (Other) \_\_\_\_\_

\* Note: Solid Door with Larsen-Loc® can be specified as Institutional Door (access only with key) by deleting the pull handle and decal.

**STEP 5: Select Optional\* Die Cut Lettering Style and Color:**

<input type="checkbox"/> Vertical	<input type="checkbox"/> Horizontal	<input type="checkbox"/> Type A

\* Die cut lettering is available at additional cost. Standard application of lettering is on the metal section of the door - not on the glazing. Decals also are available and are shipped loose for jobsite application.

- Black
- White
- Red
- Other

**STEP 3: Indicate Trim and Door Material:**

- Steel
- Aluminum (AL)
- Stainless (SS)
- Other (specify) \_\_\_\_\_

**STEP 4: Indicate Trim Projection Below:**

<input type="checkbox"/> 1/4" Flat Trim Fully Recessed	<input type="checkbox"/> 1/4" Square Trim Semi-Recessed	<input type="checkbox"/> 2 1/2" Rolled Edge Semi-Recessed*	<input type="checkbox"/> 3/4" Plaster Stop Trimless †	<input type="checkbox"/> Surface Mounted

† Trimless cabinets must be installed before the drywall because their plaster stops must be behind the drywall. Trimless cabinets are not recommended for block wall installation.

\* See back of this sheet or attached sheet for Recessed Handle (required only for 4" return trims when ADA wall projection compliance is necessary)

LARSEN'S MANUFACTURING COMPANY - [www.larsensmfg.com](http://www.larsensmfg.com)

7421 Commerce Lane N.E., Minneapolis, MN 55432 Phone: (763) 571-1181 FAX: (763) 571-6900

FLORIDA DIVISION: 3130 N.W. 17<sup>th</sup> Street, Ft. Lauderdale, FL 33311 Phone: (954) 486-3325 FAX: (954) 486-3352

