



Larsen's® Fire Extinguishers- PW, WC, WM & CD Series

Submittal and Detail Sheet

PROJECT: _____ LOCATION: _____
 MODEL NUMBER: _____ QUANTITY: _____
 ARCHITECT: _____ CONTRACTOR: _____
 DATE: _____ DISTRIBUTOR: _____

PW SERIES-Pressurized Water

This unit is ideally suited for all industrial and commercial applications, where easy to use, positive on-off operation is important. Water is used as the extinguishing agent, making it highly effective on deep seated Class A fires. (Shipped empty.)

WC SERIES-Wet Chemical

Wet Chemical units are designed specifically for kitchen grease fire hazards and meet the new K class listing now required for all extinguishers installed in restaurant kitchens. They contain a special potassium acetate based, low PH agent, which leaves no chemical residue to clean up. The spray applicator wand keeps the operator at a safe distance from the fire. Larger 2-1/2 gallon unit with identical U.L. rating is available. (shipped charged)

WM SERIES-Water Mist

This unit is designated for use wherever there is a Class A hazard near electrical equipment and the environment is of paramount concern. The extinguishing agent is de-ionized water, and the wand provides greatest operator safety. There is no risk of electrical conductivity or thermal or static shock. Ideal for use in health care, data processing, telecommunication, and clean room facilities. (Shipped empty)



PW2½ WC-6L WM2½

MODEL NUMBER	NOMINAL CAPACITY	SHIPPING WEIGHT	CYLINDER DIAMETER	OVERALL HEIGHT	OVERALL WIDTH	UL RATING	STANDARD BRACKET*	OPTIONAL BRACKET*
PW2½	2½ gal.	7½ lbs.	7 in.	24½ in.	9 in.	2A	1007	B1,864
WC-6L	6 liters	23 lbs.	7 in.	25 in.	9 in.	2A:K	1007	B1
WM2½	2½ gal.	9 lbs.	7 in.	26 in.	11 in.	2A:C	1007	864

CD SERIES---Carbon Dioxide

These units contain liquid carbon dioxide under pressure. It is discharged as a white cloud of "snow," which effectively smothers a fire. Carbon dioxide is a clean, non-conductor of electricity for Class B and C fires.

MODEL NUMBER	NORMAL CAPACITY	SHIPPING WEIGHT	CYLINDER DIAMETER	OVERALL HEIGHT	OVERALL WIDTH	UL RATING	STANDARD BRACKET*	OPTIONAL BRACKET*
CD5	5 lbs.	14 lbs.	5¼ in.	17¾ in.	8¼ in.	5-B:C	546	862
CD10	10 lbs.	28¼ lbs.	7 in.	24 in.	12 in.	10-B:C	575	864
CD15	15 lbs.	37¾ lbs.	7 in.	30 in.	12 in.	10-B:C	575	864
CD20	20 lbs.	50¾ lbs.	8 in.	30 in.	13 in.	10-B:C	577	864


All carbon dioxide units feature:

- 0-ring seal, straight thread brass valve-fits all size
- Absolutely rust free aluminum cylinders
- Up to 30% lighter




CD5 CD10 CD15 CD20

STANDARD BRACKETS*



OPTIONAL BRACKETS*



***NOTE:** Standard brackets are included with all extinguishers at no additional cost. If specified, optional brackets are only available at additional cost. All of the above brackets are designed to accommodate Larsen's extinguishers. While most comparably sized extinguishers usually will function with the above brackets, Larsen's cannot assume responsibility for variations in cylinder dimensions among various extinguisher suppliers.

LARSEN'S MANUFACTURING COMPANY
 7421 Commerce Lane N.E., Mpls, MN 55432
 Phone: (763) 571-1181 FAX: (763) 571-6900
www.larsensmfg.com

FLORIDA DIVISION:
 3130 N.W. 17th Street, Ft. Lauderdale, FL 33311
 Phone: (954) 486-3325 FAX: (954) 486-3352